What is claims is:

1.   A content data acquiring system comprising:

a portable terminal which issues a content

data request for content data desired by a user, and

receives a desired content data file to reproduce said

5   desired content data from said desired content data

file;

a first server which is provided on a first

network and which can provide first content data files

written in a first language, wherein said first server

10   transmits a desired one of said first content data

files via said first network in response to said

content data request when said content data request is

destined to said first server;

a second server which is provided on a second

15   network as the Internet and which can provide second

content data files written in a HTML (hypertext markup

language) language, wherein said first language is

different from said HTML language, and said second

server transmits said desired one of said second

20   content data files via said second network when said

content data request is destined to said second

server; and

a gateway which is operatively connected with

said portable terminal and said first and second

25   servers, and transfers said content data request from

said portable terminal to said first or second server

based on said content data request, and transfers said desired content data file from said first or second server to said portable terminal.

2.   The content data acquiring system according to claim 1, wherein said first server is a WAP (wireless access protocol) server, said first language is WML (wireless markup language) language, and said

5 first network is a WAP network.

3.   The content data acquiring system according to claim 1, wherein said portable terminal is a portable phone.

4.   The content data acquiring system according to claim 1, wherein said portable terminal is a portable computer.

5.   The content data acquiring system according to claim 1, wherein said gateway comprises

        a base station which transfers said content data request from said portable terminal, and transfer

5 said desired content data file to said portable terminal; and

        a control unit which transfers said content data request transferred from said base station to said first or second server based on said content data

10 request, and transfers said desired content data file

to said base station, and

said control unit comprises:

a WML converting section which converts said

desired content data file having a HTML data format

15 and transmitted from said second server to have a WML

data format, and converts said content data request

having a WAP data format and transmitted from said

base station to have an HTML data format and transmits

said content data request having said HTML data format

20 to said second server based on said content data

request; and

a data converting section which converts said

desired content data file having said WML data format

and transmitted from said first server or said WML

25 converting section to have a WAP data format and

transmits said desired content data file to said base

station, and converts said content data request having

said WAP data format and transmitted from said base

station to have said WML data format and transmits

30 said content data request having said WML format to

said first server based on said content data request.

6. The content data acquiring system according

to claim 1, wherein said desired content data file

includes an identifier indicating a category of said

desired content data file.

7.   The content data acquiring system according to claim 6, wherein said desired content data file is classified into said category based on a size of said desired content data file.

8.   The content data acquiring system according to claim 6, wherein said desired content data file is classified into said category based on a file format of said desired content data file.

9.   The content data acquiring system according to claim 6, further comprising a peripheral device corresponding to said identifier,

wherein said portable terminal transmits said
5 desired content data file to said peripheral device such that said peripheral device reproduces said desired content data from said desired content data file.

10.   The content data acquiring system according to claim 6, further comprising a plurality of peripheral devices respectively allocated with identifiers which are different from each other,

5   wherein said portable terminal comprises:

a storage section which stores relations of one identifier and one peripheral device; and

a control section which extracts at least an

identifier from said desired content data file,

10 determines whether said extracted at least an

identifier is stored in said storage section, and

transmits said desired content data file to at least

one of said plurality of peripheral devices

corresponding to said extracted at least an identifier

15 such that said at least one peripheral device

reproduces said desired content data from said desired

content data file, when it is determined that said

extracted at least an identifier is stored in said

storage section.

11.   The content data acquiring system according

to claim 10, wherein said portable terminal reproduces

said desired content data from said desired content

data file, when it is determined that said extracted

5 at least an identifier is not stored in said storage

section.

12.   The content data acquiring system according

to claim 9, wherein said portable terminal transmits

said desired content data file to said peripheral

device or said at least one of said plurality of

5 peripheral devices through a radio channel.

13.   The content data acquiring system according

to claim 10, wherein said portable terminal further

comprises a display section, and

wherein said control section controls said

5 display section to display a menu screen in a

peripheral device setting mode,

said control section controls said display

section to display said stored relations of said

identifier and said peripheral device when a

10 confirmation item of said menu screen is selected,

said control section stores a new relation of

said identifier and said peripheral device in said

storage section when a new registration item of said

menu screen is selected,

15 said control section controls said display

section to display said relations of said identifier

and said peripheral device when a change item of said

menu screen is selected, and stores a changed relation

of said identifier and said peripheral device in said

20 storage section when the displayed relation is

changed, and

said control section deletes all said stored

relations of said identifier and said peripheral

device when a all-deletion item of said menu screen is

25 selected.

14. The content data acquiring system according

to claim 6, further comprising:

a plurality of peripheral devices connectable

to said portable terminal; and

5   a third server which is provided on said
first or second network and transmits information of
the most adaptive peripheral device to said portable
terminal based on reception data of said plurality of
peripheral devices and said identifier corresponding

10   to said desired content data file, when any of said
plurality of peripheral devices is adaptive, and
wherein said portable terminal transmits said
reception data to said third server and receives said
information of the most adaptive peripheral device and

15   transmits said desired content data file to the most
adaptive peripheral device based on said information.

15.   The content data acquiring system according
to claim 14, wherein when said portable terminal
transmits only said identifier or when there is no
adaptive peripheral device in said reception data,

5   said third server transmits a list of adaptive
peripheral devices to said portable terminal.

16.   A data processing terminal connectable a
plurality of peripheral devices, comprising:
a transmitting section which transmits a
radio signal to a base station;

5   a receiving section which receives a radio
signal from said base station;

a storage section which stores relations of
an identifier and a peripheral device;

a reproducing section which can reproduce

10 desired content data from a desired content data file;

an interfacing section which can transmit and
receive a signal; and

a control section which controls said
transmitting section to transmit a content data

15 request to said base station, extracts at least an
identifier from said desired content data file
received by said receiving section in response to said
content data request, searches said storage section to
determine whether said extracted at least an

20 identifier is stored in said storage section, and
transmits said desired content data file to said
peripheral device adaptive for said al least an
identifier without reproduction of said desired
content data by said reproducing section, when it is

25 determined that said extracted at least an identifier
is stored in said storage section.

17.   The data processing terminal according to
claim 16, wherein said control section controls said
reproducing section to reproduce said desired content
data from said desired content data file when it is

5 determined that said extracted at least an identifier
is not stored in said storage section.

18.   The data processing terminal according to claim 16, wherein said interfacing section is detachable.

19.   The data processing terminal according to claim 16, wherein said interfacing section transmits said desired content data file to said adaptive peripheral device through a radio channel.

20.   The data processing terminal according to claim 16, wherein said identifier indicates a category of said desired content data file.

21.   The data processing terminal according to claim 20, wherein said desired content data file is classified into said category based on a size of said desired content data file.

22.   The data processing terminal according to claim 20, wherein said desired content data file is classified into said category based on a file format of said desired content data file.

23.   The data processing terminal according to claim 16, wherein said data processing terminal has a portable phone function.

24.   The data processing terminal according to claim 16, wherein said control section controls a display section of said reproducing section to display a menu screen in a peripheral device setting mode,

5   said control section controls said display section to display said stored relations of said identifier and said peripheral device when a confirmation item of said menu screen is selected,

        said control section stores a new relation of

10 said identifier and said peripheral device in said storage section when a new registration item of said menu screen is selected, and said new relation is inputted,

        said control section controls said display

15 section to display said relations of said identifier and said peripheral device when a change item of said menu screen is selected, and stores a changed relation of said identifier and said peripheral device in said storage section when the displayed relation is

20 changed, and

        said control section deletes all said stored relations of said identifier and said peripheral device when a all-deletion item of said menu screen is selected.

25.   The data processing terminal according to claim 16, wherein said control section transmits

device data indicating said peripheral devices

connected to said data processing terminal an inquiry

5 server and receives information of the most adaptive

peripheral device in response to said device data, and

transmits said desired content data file to the most

adaptive peripheral device based on said information.

26. A content data acquiring system comprising:

a peripheral device corresponding to an

identifier;

a portable terminal which issues a content

5 data request for content data desired by a user, and

receives a desired content data file to extract said

identifier from said desired content data file and

controls said peripheral device to reproduce said

desired content data from said desired content data

10 file;

a server which is provided on a network and

which transmits a desired content data file via said

network in response to said content data request;

a gateway which is connected to said parable

15 terminal and said server and transfers said content

data request from said portable terminal to said

server, and transfers said desired content data file

from said server to said portable terminal.

27. The content data acquiring system according

to claim 26, wherein said server is a WAP (wireless access protocol) server, said desired content data file is written in a WML (wireless markup language)

5   language, and said network is a WAP network.

28.   The content data acquiring system according to claim 26, wherein said gateway comprises:

a base station which transfers said content data request from said portable terminal, and

5   transfers said desired content data file to said portable terminal; and

a control unit which transfers said content data request transferred from said base station to said server, and transfers said desired content data

10   file from said server to said base station, and

said control unit comprises:

a data converting section which converts said desired content data file having said WML data format and transmitted from said server to have a WAP data

15   format and transmits said desired content data file having said WAP data format to said base station, and converts said content data request having said WAP data format and transmitted from said base station to have said WML data format and transmits said content

20   data request having said WML format to said server based on said content data request.

29.   The content data acquiring system according
to claim 28, wherein said server is an Internet
server, said desired content data file is written in
an HTML (Hypertext markup language) language, and said
5   network is the Internet.

30.   The content data acquiring system according
to claim 29, wherein said control unit comprises:
        a converting section which converts said
desired content data file having a HTML data format
5   and transmitted from said server to have a WML data
format, converts said desired content data file having
said WML data format to have a WAP data format and
transmits said desired content data file having said
WAP data format to said base station, and converts
10 said content data request having said WAP data format
and transmitted from said base station to have an HTML
data format and transmits said content data request
having said HTML data format to said server based on
said content data request.

31.   The content data acquiring system according
to claim 26, wherein said portable terminal is a
portable phone.

32.   The content data acquiring system according
to claim 26, wherein said portable terminal is a

portable computer.

33.   The content data acquiring system according to claim 26, wherein said desired content data file is classified to have said identifier based on a size of said desired content data file.

34.   The content data acquiring system according to claim 26, wherein said desired content data file is classified to have said identifier based on a file format of said desired content data file.

35.   The content data acquiring system according to claim 26, further comprising:

a plurality of peripheral devices connectable to said portable terminal; and

5   an inquiry server which is provided on said network and transmits information of peripheral device the most adaptive for reproduction of said desired content data to said portable terminal based on device data of said plurality of peripheral devices and said

10   identifier extracted from said desired content data file, when any of said plurality of peripheral devices is adaptive, and

wherein said portable terminal transmits said device data to said inquiry server and receives said

15   information of the most adaptive peripheral device and

transmits said desired content data file to the most

adaptive peripheral device based on said information.

36.   The content data acquiring system according

to claim 35, wherein when said portable terminal

transmits only said identifier or when there is no

adaptive peripheral device in said device data, said

5 inquiry server transmits a list of adaptive peripheral

devices to said portable terminal.